

Product Specifications

In-Transit Temperature Recorder

| | |
|--|--|
| Temperature Range | Standard Model: -20°F to 100°F (-29°C to 38°C) High Range Model: 32°F to 150°F (0°C to 65°C) Low Range Model: -40°F to 80°F (-40°C to 27°C) |
| Accuracy | ±2°F (±1°C) or better |
| Sensor | Bi-metal coil |
| Chart | Pressure sensitive, total length 36 inches (91.4cm), dual scale °F/°C |
| Drive | Solid state quartz motor |
| Time Keeping Accuracy/Clock Motor | Average ±20 seconds a month |
| Battery | AA Alkaline - high range models AA Carbon Zinc - standard models AA Lithium - low range model |
| Shelf Life | 3 years |
| Size | 5.5 in (L) x 4 in (W) x 2.5 in (H), 13.5 cm (L) x 10 cm (W) x 6.3 cm (H) |
| Weight | 6.98oz. (198g) |
| Case Lot Size/ Weight | 20 recorders per case/ 11lbs. (4.9kg) |
| Certification/cali- bration | CE mark by T.U.V., traceable to N.I.S.T. |
| DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system | |
| PATENT NO. 4,990,940 | |



| Models | 5-Day | 10-Day | 20-Day | 30-Day | 40-Day | 60-Day | 90-Day |
|-----------------------|-------|--------|--------|--------|--------|--------|--------|
| Standard Range | 16000 | 16100 | 16200 | 16300 | 16350 | 16400 | 16500 |
| High Range | 16002 | 16102 | 16202 | 16302 | | 16402 | 16502 |
| Low Range | 16004 | 16104 | 16203 | | | 16403 | |

- New 2 part document for ease of use
- New improved pull tab designed to make it easier to START
- Dual scale °F/°C chart
- Trilingual operation instructions (English, Spanish, Chinese)
- Patented design guarantees recording trace stops at end of trip
- Serial number on each unit for traceability
- Thermoformed top case for faster temperature response and reduced weight of unit



SS 16000-X 18J1